



# YOKOGAWA AXF FLOW METER CONFIGURATION REQUEST

**PHONE:** 08 9500 9120  
**FAX:** 08 6323 1115  
**EMAIL:** [admin@instrowest.com.au](mailto:admin@instrowest.com.au)  
**WEBSITE:** [www.instrowest.com.au](http://www.instrowest.com.au)

Tag Number		(Maximum 16 Characters)
Description		
Flow Dampening		(0.1 to 200.0 Seconds)
Base Flow Unit		
Base Time Unit		
Flow Span		(Between 0-32000 Units)
Flow Decimal Point		
Pulse Output Required?	Yes No	
Pulse Unit		
Pulse Scale		(Between 0-32000 Units)
Pulse Width		
Display Select	Off Flow Rate (%) Flow Rate Flow Rate (mA) Flow Rate (Bar) Forward Total Reverse Total Dif Total Tag No Adhesion Check	(Choose 1, 2 or 3 Options)

The Yokogawa AXF is among the the most advanced magnetic flow transmitters in the world. These transmitters have a lot of extra functionality not listed above.

Options include functions such as mass flow with either a density input or programmed density, alarm functions, adhesion detection and alarming, plus others.

This is just a basic set up, if a more detailed set up is required please contact Instrowest to arrange a service technician to assist.

